

SIROCCO 1080

Hot and Cold laminator up to 1,08 m (42.5")

Sirocco 1080 is an entry level laminator that can handle demanding job runs. Its performance surpasses the requirements of Printers & Finishers offering standard lamination services within a reasonable budget.














- Lamination, adhesive setting and mounting
- * 40°c (104°F) recommended temperature for optimised results with these laminating films

Thermal films:

- Encapsulation with lamination films up to 125 microns thickness (5 mil)
- Encapsulation with opaque backing substrates
- Use of different type of film (finishing or texture) on top and bottom position

Sirocco 1080 fits into any office environment. Used as a table top laminator, it can be installed on a mobile stand, on castors with a storage space for film reels (optional).








^{**} Same temperature adjustment for the top and bottom heating rollers













SIROCCO 1080 Technical Specifications

| 4000 (40 5") |
|--|
| 1080 mm (42.5") |
| 1130 mm (44.5") |
| 54 mm (2.1 ") |
| 25 mm (1 ") |
| 125 microns / side - (5 mil) |
| yes, from 40 to160°c (104 to 320°F) |
| yes |
| nwinding yes |
| chine 3 |
| 3 - (10) |
| yes |
| yes |
| 2 |
| optional |
| optional |
| 100 |
| 2800 |
| 230V / 50Hz - 60 Hz single phase |
| 13 amps |
| L142 x D62 x H58 cm - (56"x25"x20") |
| L142 x D76 x H68 cm - (56"x30"x27") |
| (Lbs) 122 - (269) |
| 42 - (93) |
| L180 x D105 x H 100 cm - (71"x42"x40") |
| 209 - (460) |
| |
| |



KALA SAS - Parc de l'Ecotay 35 410 Nouvoitou - France

Tel.: +33 (0)2 99 37 64 64 - Fax: +33 (0)2 99 37 64 65 Internet: www.kala.fr - e-mail: info@kala.fr