

Wallpaper Sandblast (FR)

ImagePerfect™ 2412 Wallpaper Sandblast is a washable paper for wall decoration. This product has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

IP 2412

ImagePerfect™ 2412 is a structured printable wallpaper. Due to its non-woven backing, this wallpaper is very easy to apply with wallpaper paste (for non-woven liner) and has first-class removability. The printed material can be cleaned with warm water, soap and a soft sponge, and the printed graphics are also very scrub resistant. Test results can be categorised as the highest standard in the wallpaper industry. IP 2412 can be used to personalise home interiors, show rooms, trade shows, events, restaurants, hotels and many more environments.

Attention: It is important to use the matched Spandex print profile for this product as vertically applied graphics may otherwise delaminate from the substrate as a result of increased surface tension (caused by ink oversaturation). It is strongly recommended for printed media to lay flat during the drying process. Please ensure that the printed IP 2412 is completely dry before application. Please ensure that the surface is perfectly clean before application. Wallpaper paste recommendation: Henkel or Quelyd (use paste for 'non-woven' wallpaper which is readily available in most Do-It-Yourself shops).

Specifications	
DESCRIPTION	Wallpaper
COLOUR	White matt
THICKNESS	330 μ
WEIGHT	240g/m ²
TEMPERATURE RANGE	N/A
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© June 2017 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the matchcomponent ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.