

Flexan Extra Gloss 225

RESIN-COATED PAPER WITH SLP



PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	226	± 7
Thickness DIN EN ISO 534	µm	214	± 7
	mil	8,4	± 0,3
Gloss BYK (60°) ISO 2813		92	± 5
Colour Elrepho UVO (D65) ISO 2469	L	93,5	± 0,6
	a	-0,3	± 0,4
	b	-1,6	± 0,6
	delta b	11,9	± 0,6
CIE whiteness (D65/10°) min. ISO 2469		> 144	
Opacity min. ISO 2469	%	> 92	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

🟠 Inkjet solvent

🟡 Inkjet latex

🟣 Inkjet UV

BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Optimum handling properties
- High light fastness
- Outdoor durability
- Outstanding lay-flat performance
- Fast dry
- PVC free

KEY APPLICATIONS

Wall Decoration

- Posters
- Large-format photo prints

Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and outdoor applications
- POS signage

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2020